

[Home](#) ▶ [Equipment](#) ▶ [Loaders](#) ▶ [Skid-Steer Loaders](#) ▶ [S770](#)

# S770

## Skid-Steer Loader



The Bobcat® S770 skid-steer loader is loaded with performance and comfort features that can't be matched by other machines in the same size class.

- Maximum headroom and legroom
- Operator-friendly controls
- Powerful hydraulics
- Superior lift arms
- Panoramic serviceability

[Build & Quote](#)

[Contact Dealer](#)

[View Offers](#)



[Find Dealer](#)

[Download Brochure](#)

## S770 Overview

The Bobcat S770 delivers big productivity and performance for tough digging, loading, pushing, grading and other tough assignments. With a 92 hp engine, 3350 lb. Rated Operating Capacity (ROC), stronger lifting power (up to 11 feet of vertical lift) and added reach, you can easily place cargo and tackle your most demanding tasks.

## S770 Specifications

### S770 Key Specifications

Horsepower	68.6 kW
Rated Operating Capacity (ISO)	1520 kg
Operating Weight	4225 kg
Auxiliary Std Flow	87.1 l/min
Auxiliary High Flow	138.5 l/min
Joystick Control	Optional

**Engine**

Emissions Tier (EPA)	Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	68.6 kW
Turbocharged Engine	yes

**Performance**

Rated Operating Capacity (ISO)	1520 kg
Tipping Load	3039 kg
Operating Weight	4225 kg
Travel Speed	11.4 km/h
Travel Speed (2-speed option)	19.8 km/h

**Capacities**

Fuel Tank	90.5 l
-----------	--------

**Hydraulic System**

System Relief @ Quick Couplers	241.32 bar
Auxiliary Std Flow	87.1 l/min
Auxiliary High Flow	138.5 l/min

**Dimension**

Length	3597 mm
Length without Attachment	2903 mm
Length with Standard Bucket	3597 mm
Width	1831 mm
Width (with bucket)	1880 mm
Height	2065 mm
Height with Operator Cab	2065 mm
Height to Bucket Hinge Pin	3338 mm
Reach @ Maximum Height	853 mm
Turning Radius	2179 mm
Wheelbase	1227 mm

## Features

Joystick Control	Optional
Air Conditioning	Optional
Adjustable Seat	Standard
Backup Alarm	Standard
BICS System (Interlock)	Standard
Cab Enclosure	Optional
Sound Option	Optional
Cab Heater	Optional
Operating Lights	Standard
Parking Brake	Standard
Radio	Optional
Rear Window	Standard
Top Window	Standard
Lift-Arm Support	Standard
Seat Belt	Standard
Suspension Seat	Standard
Two Speed Travel	Optional
Deluxe Instrumentation	Optional
Engine Shutdown	Standard
Hydraulic Bucket Positioning	Optional
High Flow Option	Optional
Auxiliary Hydraulics	Standard
Spark Arrestor Muffler	Standard
Bob-Tach Attachment System	Standard
Power Bob-Tach	Optional
ACS (Switchable Controls)	Optional
Ride Control	Optional
Rear Hydraulics	Optional
Horn	Standard

# S770 Features & Benefits

[Expand all](#) ▾

Performance 10 ▾

Uptime Protection 7 ▾

Comfort 8 ▾

Serviceability 4 ▾

Versatility 5 ▾

# S770 Attachments

[View All Attachments](#) >



## 3-Point Adapter

Use with Category I and II implements.



## Angle Broom - 68"

Clear away dirt, dried mud, light snow and other debris.



## Auger - 35PH

Direct drive augers are id posts, piers, poles, or tre



**WARNING:** This product can expose you to chemicals including engine exhaust (including diesel engine exhaust when equipped), lead and lead compounds, mineral oils, soots, phthalates, and carbon monoxide which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.