

MT120 Specs & Compare

▲

MT120 Key Specifications

MT120

Rated Operating Capacity with Bucket (Straight)

1200 lbs

Operating Weight

3720 lbs

Auxiliary Std Flow

11.8 gpm

Width

35.6 in

Height to Bucket Hinge Pin

88.2 in

▼

Engine

MT120

Horsepower

24.5 hp

Displacement

75 cubic in

Number of Cylinders

3

▼ **Performance**

MT120

Ground Pressure (Standard Tracks)

4.3 psi

Ground Pressure (Optional Tracks)

3.9 psi

Rated Operating Capacity with Bucket (Straight)

1200 lbs

Tipping Load

3469 lbs

Operating Weight

3720 lbs

Travel Speed - Forward

4.7 mph

Travel Speed - Reverse

4.7 mph

▼ Capacities

MT120

Fuel Tank

8.1 gal

▼ Hydraulic System

MT120

Pump Capacity

12 gpm

System Relief @ Quick Couplers

3045 psi

Auxiliary Std Flow

11.8 gpm

▼ Dimensions

MT120

Length

107.34 in

Width

35.6 in

Height to Bucket Hinge Pin

88.2 in

Reach @ Maximum Height

22.2 in

Height

57.63 in

Length of track on ground

55.7 in

Track Width - Standard

9.1 in

Track Width - Wide

11 in

▼ Features

MT120

Lift-Arm Support

Standard

Auxiliary Hydraulics

Standard

Spark Arrestor Muffler

Standard

Bob-Tach Attachment System

Optional

Common Industry Interface

Optional

Wide Track

Optional

Neutral Start Interlocks

Not Applicable

Lift Arm Lockout With Manual Bypass

Standard

Tilt Lockout

Standard

Built-In Tie Down & Crane/Lift Locations

Standard

Machine IQ Telematics

Optional